

# FIRST CHOICE SAFETY FLOORING

## LEED POINT PROGRAM

First Choice Safety Flooring material qualifies for the following **LEED** point categories:

### **Materials and Resources:**

**1 Point** MR Credit 2.1: Construction Waste Management: Diversion of 50% construction waste from disposal received by recycling at least 50% by weight of construction, demolition and land clearing.

**1 Point** MR Credit 2.2: Diversion of 75% construction waste by allowing collection and return of job site commercial flooring waste (collection and return of job site waste is the responsibility of the end user and installation company).

**1 Point** MR Credit 4.1: Recycled Content (25%): Achieved with a minimum of 75% by weight of pre-consumer (post industrial) recycled content.

**1 Point** MR Credit 4.2: Recycled Content (50%): Achieved with a minimum of 75% by weight of pre-consumer (post industrial) recycled content.

**1 Point** MR Credit 5.1: Regional Recycled Content (20%): May be achieved so long as project is within a 500 mile radius of the First Choice Safety Flooring manufacturing facility located in Chelsea, MA.

### **Innovation and Design Process:**

**1 – 4 Points** ID Credit 1-1.4: Innovation in Design. First Choice Safety Flooring material goes beyond the **LEED** rating system to provide end users with exceptional performance. The key advantage of First Choice Safety Flooring material is that the fibrous mixture of the in-house blended PVC does not expand and contract like other non-reinforced flooring. Further, a specific additive enhances the slip resistance of our material which is homogenous and does not wear out over the life of the floor system.

**MAXIMUM potential **LEED** points from the listed categories is up to 9 points for First Choice Safety Flooring material and depending on the installation adhesives and sealants the MAXIMUM potential **LEED** points from the total commercial floor system is **10 points**.**